

Cutter



product description:

The Cutter is used for cutting polymer-optical fibres. It ensures a straight and smooth cutting surface to minimize loss of quality when connecting.

If there is visible abrasion on the blade, the cutter should no longer be used, as this causes losses in the POF and can result in decreased performance.



| Art-No.: | Type | Content | PU | Overall-width mm | Overall-height mm | Depth mm | PU/kg |
|------------|------|---------|-----|------------------|-------------------|----------|-------|
| 257 90 001 | 2.2 | 5 | PCS | 44 | 31 | 8 | 0,059 |

| Accessories | | |
|--|--|------------|
| Medium duty corrugated plastic conduit | FFKuS DATALIGHT® | 257 10 025 |
| Connector | Connector 2.2 | 257 50 002 |
| Data line | Duplex Fibre 2.2 DATALIGHT® | 257 80 102 |
| Switch | Switch 6+2-Port 100 DATALIGHT® | 257 30 126 |
| Network access socket | LAN Access Point 2-Port 100 DATALIGHT® | 257 20 121 |
| Network access socket | WLAN Access Point 100 DATALIGHT® | 257 21 111 |

Hotline

Since technical developments cannot be foreseen, electrical installations should provide the possibility to be expanded at any time.
If you generously install a system of unused conduits today, you can easily expand your electrical installations later.
You save lots of time, money and effort!

We are happy to help you with any technical questions.
Prompt information can be obtained from our technical consultants at +49 9525 88-8123.